



215 Vineyard Court, Morgan Hill, CA 95037
 PHONE (408) 778-4200 FAX (408) 778-4300
 Website: MarkiMicrowave.com

Note: Negative Bias not applicable to all models

Dimensions: .236 [5.99], .282 [7.16], .38 Typ [9.6], .055 [1.40], .480 [12.19], .590 [14.99], .295 [7.49], .800 [20.32], .20 [5.2]

Electrical connections: -5, +5, D/C, Model #, SMA Female, 2.92 mm Female, Ø.080 [2.03] Thru, 4 PL

Port	Connector	Models >26.5 GHz
F	SMA Female	SMA Female
2F	SMA Female	2.92 mm Female

It is recommended that the negative bias be applied before or concurrent with the positive bias.

Spacer Plate

Weight: 15 grams typ

Dimensions: .050 [1.27], .700 [17.78], .06 [1.5] Rad 4 PL, .055 [1.40], .480 [12.19], .236 [5.99], .590 [14.99], .295 [7.49], .177 [4.50], .282 [7.16], .236 [5.99], .800 [20.32], .10 Typ [2.5], .095 [2.14], .190 [4.83], .400 [10.16]

Electrical connections: -5, +5, Model #, SMA Female, 2.92 mm Female, Ø.015±.001 Pin [.38] 2 PL, Ø.080 [2.03] Thru, 4 PL, 0-80 UNF-2B Thru, 4 PL, 2-56 UNC-2B x .12 Deep 4 PL, .400 Typ [10.16]

Weight: 8 grams typ

A-Style Amplified Doubler Outline

Projection		XXX=±.005 XX=±.02
	Inch [mm]	