

GaAs MMIC Double Balanced Mixer

MM1-0832H

1. Device Overview

1.1 General Description

The MM1-0832H is a GaAs MMIC double balanced mixer that is designed for and operates at X through K bands. MM1-0832H is a high linearity K band mixer that works well as both an up and down converter. This mixer offers low conversion loss and high LO to RF isolations over a broadband X to K band. The sister component MM1-0832L is recommended for low power applications. The MM1-0832H is available as both a wire bondable die and as a connectorized module. For a list of recommended LO driver amps for all mixers and IQ mixers, see [here](#).



Die



Module


1.2 Features

- Low cost K band mixer
- Broadband Performance
- RoHS Compliant

1.3 Applications

- Mobile test and measurement equipment
- Radar and satellite Communications
- 5G Transceivers

1.4 Functional Block Diagram



1.5 Part Ordering Options¹

Part Number	Description	Package	Green Status	Product Lifecycle	Export Classification
MM1-0832HCH-2	Wire bondable die	CH	RoHS	Active	EAR99
MM1-0832HS	Connectorized module	S		Active	EAR99

¹ Refer to our [website](#) for a list of definitions for terminology presented in this table.

Table of Contents

1. Device Overview	1	3.5 Electrical Specifications	5
1.1 General Description	1	3.6 Typical Performance Plots	6
1.2 Features	1	3.6.1 Typical Performance Plots: IP3 ..	8
1.3 Applications	1	3.6.2 Typical Performance Plots: LO	
1.4 Functional Block Diagram	1	Harmonic Isolation.....	9
1.5 Part Ordering Options.....	1	3.6.3 Typical Spurious Performance:	
2. Port Configurations and Functions	3	Down-Conversion	10
2.1 Port Diagram.....	3	3.6.4 Typical Spurious Performance: Up-	
2.2 Port Functions	3	Conversion	10
3. Specifications	4	4. Die Mounting Recommendations	11
3.1 Absolute Maximum Ratings.....	4	4.1 Mounting and Bonding	
3.2 Package Information	4	Recommendations	11
3.3 Recommended Operating Conditions .	4	4.2 Handling Precautions	11
3.4 Sequencing Requirements	4	4.3 Bonding Diagram	12
		5. Mechanical Data	13
		5.1 CH Package Outline Drawing	13
		5.2 S Package Outline Drawing.....	13


Revision History

Revision Code	Revision Date	Comment
-	October 2018	Datasheet Initial Release





2. Port Configurations and Functions

2.1 Port Diagram

A top-down view of the MM1-0832H's CH package outline drawing is shown below. The MM1-0832H has the input and output ports given in Port Functions. The MM1-0832H can be used in either an up or down conversion. For configuration A, input the LO into port 1, use port 3 for the RF, and port 2 for the IF. For configuration B, input the LO into port 3, use port 1 for the RF, and port 2 for the IF.



2.2 Port Functions

Port	Function	Description	Equivalent Circuit for Package
Port 1	LO (Configuration A) RF (Configuration B)	Port 1 is DC open for the CH and S packages.	P1 
Port 2	IF	Port 2 is diode connected for the CH and S packages.	P2 
Port 3	RF (Configuration A) LO (Configuration B)	Port 3 is DC open for the CH and S packages.	P3 
GND	Ground	CH package ground path is provided through the substrate and ground bond pads. S package ground provided through metal housing and outer coax conductor.	GND 

3. Specifications

3.1 Absolute Maximum Ratings

The Absolute Maximum Ratings indicate limits beyond which damage may occur to the device. If these limits are exceeded, the device may be inoperable or have a reduced lifetime.

Parameter	Maximum Rating	Units
Port 1 DC Current	N/A	mA
Port 2 DC Current	N/A	mA
Power Handling, at any Port	+30	dBm
Operating Temperature	-55 to +100	°C
Storage Temperature	-65 to +125	°C

3.2 Package Information

Parameter	Details	Rating
ESD	Human Body Model (HBM), per MIL-STD-750, Method 1020	1A
Weight	S Package	12 g

3.3 Recommended Operating Conditions

The Recommended Operating Conditions indicate the limits, inside which the device should be operated, to guarantee the performance given in Electrical Specifications. Operating outside these limits may not necessarily cause damage to the device, but the performance may degrade outside the limits of the electrical specifications. For limits, above which damage may occur, see Absolute Maximum Ratings.

	Min	Nominal	Max	Units
T _A , Ambient Temperature	-55	+25	+100	°C
LO Input Power	+11		+20	dBm

3.4 Sequencing Requirements

There is no requirement to apply power to the ports in a specific order. However, it is recommended to provide a 50Ω termination to each port before applying power. This is a passive diode mixer that requires no DC bias.

3.5 Electrical Specifications

The electrical specifications apply at $T_A=+25^{\circ}\text{C}$ in a 50Ω system. Typical data shown is for the connectorized S package mixer used in the forward direction with a +15 dBm sine wave input. Specifications shown for configuration A (B).









Min and Max limits apply only to our connectorized units and are guaranteed at $T_A=+25^{\circ}\text{C}$. All bare die are 100% DC tested and visually inspected.








Parameter		Test Conditions	Min	Typical	Max	Units
RF (Port 3) Frequency Range			8		32	GHz
LO (Port 1) Frequency Range			8		32	
I (Port 2) Frequency Range			0		12	
Conversion Loss (CL) ²		RF/LO = 8 - 32 GHz I = DC - 4 GHz		7.6 (9)	9.5 (10.5)	dB
		RF/LO = 8 - 32 GHz I = 3 - 12 GHz		9.5 (11)		
Noise Figure (NF) ³		RF/LO = 8 - 32 GHz I = DC - 0.2 GHz		8		dB
Isolation	LO to RF	RF/LO = 8 - 32 GHz		50		dB
	LO to IF	IF/LO = 8 - 32 GHz		33		
	RF to IF	RF/IF = 8 - 32 GHz		35		
Input IP3 (IIP3)		RF/LO = 8 - 32 GHz I = DC - 0.2 GHz		+22.8 (+23.7)		dBm
Input 1 dB Gain Compression Point (P1dB)				+9 (+11)		dBm

² Measured as a down converter to a fixed 91MHz IF.







³ Mixer Noise Figure typically measures within 0.5 dB of conversion loss for IF frequencies greater than 5 MHz.

3.6 Typical Performance Plots











3.6.1 Typical Performance Plots: IP3



3.6.2 Typical Performance Plots: LO Harmonic Isolation



3.6.3 Typical Spurious Performance: Down-Conversion

Typical spurious data is provided by selecting RF and LO frequencies ($\pm m \cdot \text{LO} \pm n \cdot \text{RF}$) within the RF/LO bands, to create a spurious output within the IF band. The mixer is swept across the full spurious band and the mean is calculated. The numbers shown in the table below are for a -10 dBm RF input. Spurious suppression is scaled for different RF power levels by $(n-1)$, where “n” is the RF spur order. For example, the 2RF x 2LO spur is 70 dBc for a -10 dBm input, so a -20 dBm RF input creates a spur that is $(2-1) \times (-10 \text{ dB})$ lower, or 80 dBc. Data is shown for the frequency plan in 3.6 Typical Performance.

Typical Down-conversion spurious suppression (dBc): Config A (B)

-10 dBm RF Input	0xLO	1xLO	2xLO	3xLO	4xLO	5xLO
1xRF	27 (24)	Reference	27 (37)	14 (14)	33 (40)	N/A
2xRF	77 (86)	61 (48)	70 (72)	62 (53)	69 (71)	58 (54)
3xRF	100 (104)	61 (62)	82 (90)	71 (75)	74 (91)	67 (73)
4xRF	121 (125)	98 (94)	110 (111)	109 (104)	108 (113)	108 (102)
5xRF	N/A	115 (108)	115 (123)	119 (126)	120 (125)	118 (121)

3.6.4 Typical Spurious Performance: Up-Conversion

Typical spurious data is taken by mixing an input within the IF band, with LO frequencies ($\pm m \cdot \text{LO} \pm n \cdot \text{IF}$), to create a spurious output within the RF output band. The mixer is swept across the full spurious output band and the mean is calculated. The numbers shown in the table below are for a -10 dBm IF input. Spurious suppression is scaled for different IF input power levels by $(n-1)$, where “n” is the IF spur order. For example, the 2IFx1LO spur is typically 68 dBc for a -10 dBm input with a sine-wave LO, so a -20 dBm IF input creates a spur that is $(2-1) \times (-10 \text{ dB})$ lower, or 78 dBc. Data is shown for the frequency plan in 3.6 Typical Performance.

Typical Up-conversion spurious suppression (dBc): Config A (B)

-10 dBm RF Input	0xLO	1xLO	2xLO	3xLO	4xLO	5xLO
1xIF	28 (24)	Reference	28 (38)	15 (12)	32 (39)	18 (24)
2xIF	68 (60)	68 (71)	58 (51)	60 (73)	51 (49)	59 (77)
3xIF	86 (95)	66 (70)	76 (88)	68 (67)	71 (86)	53 (55)
4xIF	111 (100)	108 (109)	97 (93)	102 (113)	92 (100)	103 (111)
5xIF	110 (129)	109 (115)	116 (129)	104 (105)	118 (125)	106 (106)

4. Die Mounting Recommendations

4.1 Mounting and Bonding Recommendations

Marki MMICs should be attached directly to a ground plane with conductive epoxy. The ground plane electrical impedance should be as low as practically possible. This will prevent resonances and permit the best possible electrical performance. Datasheet performance is only guaranteed in an environment with a low electrical impedance ground.

Mounting - To epoxy the chip, apply a minimum amount of conductive epoxy to the mounting surface so that a thin epoxy fillet is observed around the perimeter of the chip. Cure epoxy according to manufacturer instructions.

Wire Bonding - Ball or wedge bond with 0.025 mm (1 mil) diameter pure gold wire. Thermosonic wirebonding with a nominal stage temperature of 150 °C and a ball bonding force of 40 to 50 grams or wedge bonding force of 18 to 22 grams is recommended. Use the minimum level of ultrasonic energy to achieve reliable wirebonds. Wirebonds should be started on the chip and terminated on the package or substrate. All bonds should be as short as possible <0.31 mm (12 mils).

Circuit Considerations – 50 Ω transmission lines should be used for all high frequency connections in and out of the chip. Wirebonds should be kept as short as possible, with multiple wirebonds recommended for higher frequency connections to reduce parasitic inductance. In circumstances where the chip more than .001" thinner than the substrate, a heat spreading spacer tab is optional to further reduce bondwire length and parasitic inductance.

4.2 Handling Precautions

General Handling


Chips should be handled with care using tweezers or a vacuum collet. Users should take precautions to protect chips from direct human contact that can deposit contaminants, like perspiration and skin oils on any of the chip's surfaces.

Static Sensitivity

GaAs MMIC devices are sensitive to ESD and should be handled, assembled, tested, and transported only in static protected environments.


Cleaning and Storage: Do not attempt to clean the chip with a liquid cleaning system or expose the bare chips to liquid. Once the ESD sensitive bags the chips are stored in are opened, chips should be stored in a dry nitrogen atmosphere.

4.3 Bonding Diagram




5. Mechanical Data

5.1 CH Package Outline Drawing



1. CH Substrate material is 0.004 in thick GaAs.
2. I/O trace finish is 4.2 microns Au. Ground plane finish is 5 microns Au.

5.2 S Package Outline Drawing



Marki Microwave reserves the right to make changes to the product(s) or information contained herein without notice.
 Marki Microwave makes no warranty, representation, or guarantee regarding the suitability of its products for any particular purpose, nor does Marki Microwave assume any liability whatsoever arising out of the use or application of any product.