


## GaAs DOUBLE-BALANCED MIXER

## MM1-1240S

The MM1-1240S is a passive double balanced MMIC mixer. It features excellent conversion loss, superior isolations and spurious performance across a broad bandwidth, in a highly miniaturized form factor. Accurate, nonlinear simulation models are available for Microwave Office® through the Marki Microwave PDK. The MM1-1240S is available as a wire bondable chip or in a connectorized package. The MM1-1240S is a superior alternative to Marki Microwave carrier and packaged M1 and M9 mixers.



### Features

- Compact Chip Style Package (0.054" x 0.046"x0.004")
- CAD Optimized for Superior Isolation and Spurious Response
- Broadband Performance
- Excellent Unit-to-Unit Repeatability
- Fully nonlinear software models available with Marki PDK for Microwave Office®
- RoHS Compliant
- Recommended Amplifier Module: [AMM-6702UC](#)
- Recommended Amplifier Die: [AMM-6702CH](#)

**Electrical Specifications** - Specifications guaranteed from -55 to +100°C, measured in a 50Ω system. Specifications are shown for Configurations A (B). See page 2 for port locations. All bare die are 100% DC tested and 100% visual inspected. RF testing is performed on a sample basis to verify conformance to datasheet guaranteed specifications. Consult factory for more information.

Parameter	LO (GHz)	RF (GHz)	IF (GHz)	Min	Typ	Max	LO drive level (dBm)	
Conversion Loss	12-40		DC-0.2		8 (9)	14 (16)	+20 (+20)	
			0.2-12		11			
Isolation (dB) LO-RF LO-IF RF-IF						See Plots		Config. A: +18 to +23 Config. B: +18 to +23
Input 1 dB Compression (dBm)						+14 +14		
Input Two-Tone Third Order Intercept Point (dBm)					+25 +25			

### Part Number Options

Package Styles		Examples		
Connectorized <sup>1, 3</sup>	S	MM1-1240SCH-2, MM1-1240SS		
Chip <sup>2, 3</sup> (RoHS)	CH-2	<u>MM1-1240</u> (Model)	<u>S</u> (Diode Option)	<u>CH-2</u> (Package)

<sup>1</sup>Connectorized package consists of chip package wire bonded to a substrate, equivalent to an evaluation board.

<sup>2</sup>Chip package connects to external circuit through wire bondable gold pads.

<sup>3</sup>Note: For port locations and I/O designations, refer to the drawings on page 2 of this document.




# GaAs DOUBLE-BALANCED MIXER

Page 2


# MM1-1240S

LO/RF 12 to 40 GHz

IF DC to 12 GHz




**Configuration A**




**Configuration B**

1. Configuration A/B refer to the same part number (MM1-1240S) used in one of two different ways for optimal spurious performance. For the lowest conversion loss, use the mixer in Configuration A (port 1 as the LO input, port 3 as the RF input or output). If you need to use a lower LO drive, use the mixer in Configuration B (port 1 as the RF input or output, port 3 as the LO input). For optimal spurious suppression, experimentation or simulation is required to choose between Configuration A and B. For more information, [see here](#).



1. CH Substrate material is .004 in thick GaAs.
2. I/O trace finish is 2.6 microns Au. Ground plane finish is 5 microns Au.
3. Wire Bonding - Ball or wedge bond with 0.025 mm (1 mil) diameter pure gold wire. Thermosonic wirebonding with a nominal stage temperature of 150 °C and a ball bonding force of 40 to 50 grams or wedge bonding force of 18 to 22 grams is recommended. Use the minimum level of ultrasonic energy to achieve reliable wirebonds. Wirebonds should be started on the chip and terminated on the package or substrate. All bonds should be as short as possible <0.31 mm (12 mils).









# GaAs DOUBLE-BALANCED MIXER

Page 3

# MM1-1240S

LO/RF 12 to 40 GHz  
IF DC to 12 GHz

Typical Performance









# GaAs DOUBLE-BALANCED MIXER

Page 4

# MM1-1240S

LO/RF 12 to 40 GHz  
IF DC to 12 GHz

## Typical Performance









# GaAs DOUBLE-BALANCED MIXER

Page 5

# MM1-1240S

LO/RF 12 to 40 GHz  
IF DC to 12 GHz

## Typical Performance



# GaAs DOUBLE-BALANCED MIXER

# MM1-1240S

Page 6

LO/RF 12 to 40 GHz  
IF DC to 12 GHz

### Downconversion Spurious Suppression

Spurious data is taken by selecting RF and LO frequencies ( $\pm mLO \pm nRF$ ) within the RF/LO bands, to create a spurious output within the IF output band. The mixer is swept across the full spurious band and the mean is calculated. The numbers shown in the table below are for a -10 dBm RF input. Spurious suppression is scaled for different RF power levels by (n-1), where “n” is the RF spur order. For example, the 2RFx2LO spur is 63 dBc for the A configuration for a -10 dBm input, so a -20 dBm RF input creates a spur that is (2-1) x (-10 dB) dB lower, or 73 dBc.

**Typical Downconversion Spurious Suppression (dBc): A Configuration (B Configuration) <sup>4</sup>**

-10 dBm RF Input	0xLO	1xLO	2xLO	3xLO	4xLO	5xLO
1xRF	34 (14)	Reference	21 (24)	15 (11)	37 (23)	N/A
2xRF	72 (73)	57 (61)	63 (65)	62 (60)	57 (64)	63 (60)
3xRF	86 (86)	69 (85)	78 (85)	73 (76)	77 (87)	71 (76)
4xRF	N/A	104 (125)	114 (118)	104 (110)	107 (113)	109 (116)
5xRF	N/A	99 (136)	126 (131)	123 (129)	121 (129)	126 (128)

### Upconversion Spurious Suppression

Spurious data is taken by mixing an input within the IF band, with LO frequencies ( $\pm mLO \pm nIF$ ), to create a spurious output within the RF output band. The mixer is swept across the full spurious output band and the mean is calculated. The numbers shown in the table below are for a -10 dBm IF input. Spurious suppression is scaled for different IF input power levels by (n-1), where “n” is the IF spur order. For example, the 2IFx1LO spur is typically 65 dBc for the A configuration for a -10 dBm input, so a -20 dBm IF input creates a spur that is (2-1) x (-10 dB) dB lower, or 75 dBc.

**Typical Upconversion Spurious Suppression (dBc): A Configuration (B Configuration) <sup>4</sup>**

-10 dBm IF Input	0xLO	1xLO	2xLO	3xLO	4xLO	5xLO
1xIF	29 (16)	Reference	29 (32)	17 (11)	31 (27)	24 (21)
2xIF	65 (66)	65 (69)	59 (59)	65 (58)	59 (67)	56 (61)
3xIF	100 (90)	77 (70)	74 (77)	71 (71)	67 (71)	73 (72)
4xIF	114 (108)	107 (105)	101 (99)	105 (105)	99 (100)	92 (108)
5xIF	124 (119)	118 (116)	115 (117)	124 (123)	113 (118)	106 (115)

## GaAs DOUBLE-BALANCED MIXER

Page 7

**MM1-1240S**

**LO/RF 12 to 40 GHz  
IF DC to 12 GHz**

### Mounting and Bonding Recommendations

Marki MMICs should be attached directly to a ground plane with conductive epoxy. The ground plane electrical impedance should be as low as practically possible and the epoxy should have high thermal conductivity. This will prevent resonances and permit the best possible electrical performance. Datasheet performance is only guaranteed in an environment with a low electrical impedance ground. MMICs with high power dissipation, particularly those with high DC power requirements, also require a thermally conductive ground plane with a thermally conductive epoxy attachment.

**Mounting** - To epoxy the chip, apply a minimum amount of conductive epoxy to the mounting surface so that a thin epoxy fillet is observed around the perimeter of the chip. Cure epoxy according to manufacturer instructions.

**Wire Bonding** - Ball or wedge bond with 0.025 mm (1 mil) diameter pure gold wire. Thermosonic wirebonding with a nominal stage temperature of 150 °C and a ball bonding force of 40 to 50 grams or wedge bonding force of 18 to 22 grams is recommended. Use the minimum level of ultrasonic energy to achieve reliable wirebonds. Wirebonds should be started on the chip and terminated on the package or substrate. All bonds should be as short as possible <0.31 mm (12 mils).

**Circuit Considerations** – 50 ohm transmission lines should be used for all high frequency connections in and out of the chip. Wirebonds should be kept as short as possible, with multiple wirebonds recommended for higher frequency connections to reduce parasitic inductance. In circumstances where the chip more than .001" thinner than the substrate, a heat spreading spacer tab is optional to further reduce bondwire length and parasitic inductance.


### Handling Precautions

**General Handling:** Chips should be handled with a vacuum collet when possible, or with sharp tweezers using well trained personnel. The surface of the chip is fragile and should not be contacted if possible.

**Static Sensitivity:** GaAs MMIC devices are subject to static discharge, and should be handled, assembled, tested, and transported only in static protected environments.

**Cleaning and Storage:** Do not attempt to clean the chip with a liquid cleaning system or expose the bare chips to liquid. Once the ESD sensitive bags the chips are stored in are opened, chips should be stored in a dry nitrogen atmosphere.

### Bonding Diagram






# GaAs DOUBLE-BALANCED MIXER

Page 8

# MM1-1240S

LO/RF 12 to 40 GHz  
IF DC to 12 GHz

Port	Description	DC Interface Schematic
Port 1	Port 1 is DC short to ground and AC matched to 50 Ohms from 12 to 40 GHz. Blocking capacitor is optional.	
Port 2	Port 2 is DC coupled to the diodes. Blocking capacitor is optional.	
Port 3	Port 3 is DC open and AC matched to 50 Ohms from 12 to 40 GHz. Blocking capacitor is optional.	

Absolute Maximum Ratings	
Parameter	Maximum Rating
Port 1 DC Current	15 mA
Port 3 DC Current	N/A
Port 2 DC Current	24 mA
RF Power Handling (RF+LO)	+28 dBm at +25°C, derated linearly to +21 dBm at +100°C
Operating Temperature	-55°C to +100°C
Storage Temperature	-65°C to +125°C

**DATA SHEET NOTES:**

- Mixer Conversion Loss Plot IF frequency is 91 MHz.
- Mixer Noise Figure typically measures within 0.5 dB of conversion loss for IF frequencies greater than 5 MHz.
- Conversion Loss typically degrades less than 0.5 dB at +100°C and improves less than 0.5 dB at -55°C.
- Unless otherwise specified, data is taken with +20 dBm LO drive.
- Specifications are subject to change without notice. Contact Marki Microwave for the most recent specifications and data sheets.
- Catalog mixer circuits are continually improved. Configuration control requires custom mixer model numbers and specifications.





## GaAs DOUBLE-BALANCED MIXER

Page 8

**MM1-1240S**

LO/RF 12 to 40 GHz  
IF DC to 12 GHz

### Revision History

Revision Code	Revision Date	Comment
A	October 2017	Die shrunk from 1.48 x 1.18 micron to 1.37 x 1.17 micron. Die tolerance added.

*Marki Microwave reserves the right to make changes to the product(s) or information contained herein without notice. Marki Microwave makes no warranty, representation, or guarantee regarding the suitability of its products for any particular purpose, nor does Marki Microwave assume any liability whatsoever arising out of the use or application of any product.*

© Marki Microwave, Inc.



215 Vineyard Court, Morgan Hill, CA 95037 | Ph: 408.778.4200 | Fax 408.778.4300 | [info@markimicrowave.com](mailto:info@markimicrowave.com)  
[www.markimicrowave.com](http://www.markimicrowave.com)