

## DC-BLOCK

## DCZ(M/F)24(M/F)24

### Features


- 4 kHz to 65.0 GHz
- 2.40 mm Connectors
- Non-Resonant
- Low Insertion Loss
- Convenient easy-grip jacket for effortless loosening



**Electrical Specifications** - Specifications guaranteed from -55 to +100°C, measured in a 50-Ohm system.

Parameter	Frequency Range	Min	Typ	Max	
Near DC Insertion Loss (dB)	2 kHz		3		
Insertion Loss (dB)	4 kHz to 65 GHz		.7	1.4	
VSWR			1.4		
Capacitance (μF)			1		
Rise Time (ps) <sup>1</sup>			6		
Group Delay (ps)			75		
DC Voltage (V)					16
RF Power (W)					1

<sup>1</sup>Specified as 90%/10%. Calculated from  $\tau_{balun}^2 = (\tau_{out}^2 - \tau_{in}^2)$  with a 10 Gb/s input pattern.




### Part Number Options

Please specify package style by adding to model number.

Package Style(s)	Example
DCZM24F24 (Male 2.40/Female 2.40) DCZM24M24 (Male 2.40/Male 2.40) DCZF24F24 (Female 2.40/Female 2.40)	DCZM24F24

Application Schematic



The DC blocks isolate the DC components of waveforms while minimizing loss and group delay ripple.

Typical Performance




Figure 1. Insertion Loss.




Figure 2. Return Loss.




Figure 3. Near DC Insertion Loss.




Figure 4. Group Delay.





Fig. 5. Oscilloscope measurements of the DC block with a 10 Gb/s PRBS pattern. Eye diagrams are taken with a  $2^{31}-1$  P PRBS input demonstrating minimal eye distortion/closure.

DATA SHEET NOTES:

1. Specifications are subject to change without notice. Contact Marki Microwave for the most recent specifications and data sheets.

*Marki Microwave reserves the right to make changes to the product(s) or information contained herein without notice. Marki Microwave makes no warranty, representation, or guarantee regarding the suitability of its products for any particular purpose, nor does Marki Microwave assume any liability whatsoever arising out of the use or application of any product.*