



## CONSTANT ACCELERATION

MIL-STD 883 Method 2001

**PURPOSE.** This test is used to determine the effects of constant acceleration on microelectronic devices. It is an accelerated test designed to indicate types of structural and mechanical weaknesses not necessarily detected in shock and vibration tests. It may be used as a high stress test to determine the mechanical limits of the package, internal metallization and lead system, die or substrate attachment, and other elements of the microelectronic device. By establishing proper stress levels, it may also be employed as an in-line 100 percent screen to detect and eliminate devices with lower than nominal mechanical strengths in any of the structural elements.

### Test Results

Part Type	Description	Test Condition	Sample Size	Date	Results
MEQ3-14ASM	MMIC Equalizer 14 GHz 3 dB	10000 g's Y1	5	2/19/19	Pass
MEQ6-14ASM	MMIC Equalizer 14 GHz 6 dB	10000 g's Y1	4	2/19/19	Pass
MEQ10-14ASM	MMIC Equalizer 14 GHz 10 dB	10000 g's Y1	6	2/19/19	Pass
MEQ12-7ASM	MMIC Equalizer 7 GHz 12 dB	10000 g's Y1	6	2/19/19	Pass
ML1-1850LS	Microolithic Mixer RF 18-50 GHz	10000 g's Y1	11	2/19/19	Pass
MEQ3-14ASM	MMIC Equalizer 14 GHz 3 dB	10000 g's Y1	20	2/14/19	Pass
MEQ3-20ASM	MMIC Equalizer 20 GHz 3 dB	10000 g's Y1	14	2/14/19	Pass
MEQ5-20ASM	MMIC Equalizer 20 GHz 5 dB	10000 g's Y1	16	2/14/19	Pass
MEQ6-14ASM	MMIC Equalizer 14 GHz 6 dB	10000 g's Y1	20	2/14/19	Pass
MEQ12-7ASM	MMIC Equalizer 7 GHz 12 dB	10000 g's Y1	17	2/14/19	Pass
MEQ10-14ASM	MMIC Equalizer 14 GHz 10 dB	10000 g's Y1	19	2/14/19	Pass
MM2K-0530LCH-2	MMIC Mixer RF 5-30 GHz	3000 g's Y1	12	8/15/18	Pass
M1-0420LP	Mixer RF 4-20 GHz +7 dBm A pkg	3000 g's Y1	24	12/21/17	Pass
M1-0420HP	Mixer RF 4-20 GHz +16 dBm A pkg	3000 g's Y1	24	12/21/17	Pass
MM1K-1140HCH-2	RF MMIC RF Mixer 11 - 40 GHz	3000 g's Y1	12	12/6/17	Pass
T3A Mixer	T3 Mixer with integrated amp	A = 5000 g's Y1	31	03/26/16	Pass
T3A Mixer	T3 Mixer with integrated amp	A = 5000 g's Y1	27	02/08/16	Pass
T3A Mixer	T3 Mixer with integrated amp	A = 5000 g's Y1	42	01/29/16	Pass
T3A Mixer	T3 Mixer with integrated amp	A = 5000 g's Y1	38	01/19/16	Pass
T3A Mixer	T3 Mixer with integrated amp	A = 5000 g's Y1	68	12/21/15	Pass



ML1 Mixer	Microlithic Mixer	D = 20,000 g's Y1	4	02/01/13	Pass
-----------	-------------------	-------------------	---	----------	------

*Marki Microwave reserves the right to make changes to the product(s) or information contained herein without notice. Marki Microwave makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Marki Microwave assume any liability whatsoever arising out of the use of or application of any product.*

**© Marki Microwave, Inc.**

215 Vineyard Court, Morgan Hill, CA 95037 | Ph: 408.778.4200 | Fax 408.778.4300 | [info@markimicrowave.com](mailto:info@markimicrowave.com)