



Mechanical Shock Summary

MIL-STD-202, Method 213

Test Condition J, half-sine,
30G's, 11 ms duration

PURPOSE. This test is conducted for the purpose of determining the suitability of component parts and subassemblies of electrical and electronic components when subjected to shocks such as those which may be expected as a result of rough handling, transportation and military operations. This test differs from other shock tests in this standard in that the design of the shock machine is not specified, but the half-sine and sawtooth shock pulse waveforms are specified with tolerances. The frequency response of the measuring system is also specified with tolerances.

Test Results

Part Type	Description	Sample Size	Date	Results
T3A Mixer	T3 Mixer with integrated amp 3 shocks X direction	1	6/6/16	Pass
T3A Mixer	T3 Mixer with integrated amp 3 shocks Y direction	1	6/6/16	Pass
T3A Mixer	T3 Mixer with integrated amp 3 shocks Z direction	1	6/6/16	Pass

The T3A Mixer is one of the most complicated devices built at Marki Microwave. By using this device as our qualification vehicle, it effectively qualifies all of the materials and processes used in all of our various products.

This T3 Mixer with integrated amp technology utilizes: wire bonding, epoxy die attach, PCB soldering and hermetic seal. The T3 Mixer with integrated amp contains 63/37 solder, Ferrite Cores, Bi-filar wires, 100 mil Conical coils, chip capacitors, Integrated chip Amplifier, 0402 capacitors and resistors, kovar standoffs and T3 Mixer diodes.

By similarity any product using the same assembly techniques and materials can use these results for qualification.

Marki Microwave reserves the right to make changes to the product(s) or information contained herein without notice. Marki Microwave makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Marki Microwave assume any liability whatsoever arising out of the use of or application of any product.

© Marki Microwave, Inc.

215 Vineyard Court, Morgan Hill, CA 95037 | Ph: 408.778.4200 | Fax 408.778.4300 | info@markimicrowave.com

CUSTOMER: Marki Microwave
Project File Name: Shock1.prj
Profile Name: 30G, 11mSec

